



15-06 Morlot Avenue, Fair Lawn, NJ 07410 USA Tel: (201) 796-2690 Fax: (201) 796-8818

info@articulight.com

articulight@aol.com

www.articulight.com

## GRAPHIC PROJECTORS

---

GB70™

70w Pattern and Framing Projector



The GB70 is a newly developed modular image projector making any surface communicate- day or night. It lets you place, move, and rotate projected logos, text, visual or other images on any surface, at any time.

The GB70 is ideal for store fronts, window displays, POP displays, indoor advertising, or entertainment and hospitality venues. Corporations and franchises are discovering the marketing power of this projector, and how it can save time, cut costs, and project a strong image to capture consumer attention.

The GB70 is the foundation of a new mass-market and POP marketing system that broadens creative options, improves efficiency, and lowers overall production costs. It can be used together with existing forms of POP advertising, display and promotional graphics - or replace them.

The GB70 can help centralize or decentralize corporate advertising and promotional campaigns. Create a consistent message at several locations - or tailor art to suit specific needs.

The GB70 is UL, CE and VDE listed and has an IP 20. Made in the USA- IBEW.

Create custom or standard patterns, and beam shaping equal to a 300-500 watt quartz ellipsoidal while

burning a cool 70 watts of electricity.

Each unit is equipped with an onboard lightweight electronic transformer. Typical throws range from 10-20 feet. Ideal for high ceilings, or where you need that extra punch to cut through ambient light.

Gobo size: M size.OD: 66mm, ID: 48mm.

Bezeled (for glass gobos): Outer diameter with a bezel: 66mm, outer diameter: 50.25mm, Image diameter: 46mm



#### FEATURES

Cool Operation, no fan needed  
Zoom Focus 18° - 40°  
Locking Yoke  
Stainless Steel Framing Shutters  
Built- in Pattern Slot  
Up to 12,000 Hour Lamp Life



#### SALES POINTS

- \* One time hardware investment; low servicing costs
- \* Motion provides dynamic visual impact in the MTV age.
- \* Increased return on advertising and promotional investment
- \* Enables you to create the look you want, and change it easily and quickly.
- \* Very user friendly, very easy to use
- \* Custom metal, glass or dichroic gobos are optionally available according to customer requirements.



TECHNICAL SPECIFICATIONS

Field Angle:	25°-32°
Typical Throw:	10-20 feet
Lamp Base:	G-12 bipin
Lamp Reference:	CDM70w or equivalent
Weight & Dimensions:	8 lbs: 15 3/4" Long, 6 5/8" High, 10" High with Hanging bracket, 4 1/2" Wide

MOUNTING OPTIONS:

US-1/Unitrust Adapter with 6 ft Cord and Plug  
 CM4/Canopy Mount for Junction Box  
 PC9M/Pipe Clamp: 1" to 2"  
 TA2 TA3 2 Or 3 Circuit Track Adapter

OPTIONS:

Motorized Pattern Rotator  
 CC18: Coil Cord

ACCESSORIES:  
 Q3CF: Gel Frame  
 300PHM: Pattern Holder  
 Q3D: Pattern Donut  
 SC: Safety Cable

FINISHES:  
 B Black  
 W White  
 S Silver  
 CC Custom Color

Photometric Data

18°

PROJECTION DISTANCE	10'	15'	20'
BEAM SPREAD	3'	4'	5'
FOOT CANDLES	366	182	76

25°

PROJECTION DISTANCE	10'	15'	20'
BEAM SPREAD	5'	8'	9.5'
FOOT CANDLES	272	118	56

40°

PROJECTION DISTANCE	10'	15'	20'
BEAM SPREAD	7'	9'	12'
FOOT CANDLES	115	64	45

DUE TO CONTINUOUS IMPROVEMENTS, SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE.