

# ARTICULIGHT

15-06 Morlot Avenue, Fair Lawn, NJ 07410 USA Tel: (201) 796-2690 Fax: (201) 796-8818

info@articulight.com

articulight@aol.com

www.articulight.com

## INTELLIGENT LIGHTING

---

### XL 1200 WASH



Our tradition for excellence continues with the XL 1200 WASH a powerful moving head wash light. Among many of its unique and innovative features, the XL 1200 WASH boasts an ultra quiet and smooth operating control technology, an energy saving design, LCD menu, modularized construction and an option for magnetic or electronic ballast.

#### Technical Data

##### VOLTAGES:

PR-2910 100/120/200/220/230/240V AC, 50Hz or 60Hz Electronic ballast

PR-2910M 200/220/230/240V AC, 50Hz or 60Hz Magnetic ballast

##### POWER CONSUMPTION:

PR-2910: 1500W @ 220V

PR-2910M: 1600W @ 220V

##### LAMP:

PHILIPS MSR GOLD 1200W SA/2DE

Color Temperature: 7500°K

Socket: SFc10-4

Manufacturers Rated Lamp Life: 750 Hours

Lumen Output: 100,300 lumens

##### COLORS:

Linear CYM color mixing system with Macro function

1 wheel with 6 fixed dichroic colors plus white

With variable speed bi-directional rainbow effect

Stepper/linear color changing is available

##### COLOR TEMPERATURE CORRECTION:

2 color temperature correction filters.

Linear color temperature correction ( 8 and 16 bit)

**DIMMER/SHUTTER:**

Double shutter blades, 0-100% linearly adjustable (8 and 16 bit)

**STROBE:**

0.3 – 12 F.P.S.

**HEAD MOVEMENT:**

Pan 450°, Tilt 270° (8 and 16 bit)

**ZOOM:**

10°--42° linear zoom and 15°--42° linearly adjustable (8 and 16 bit)

**CONTROL:**

DMX512, Short mode: 14 channels. Standard mode: 17 channels, Extended Mode: 37 self testing mode

**OTHER FUNCTIONS:**

Sensor system for fault diagnosis  
Isolation protection for DMX signal  
Network interface (reversed)  
In conformity with CE standard and ROHS directive.

**DISPLAY:**

LCD, brightness and contrast adjustable, display setting without main power, Projector usage time display, lamp time display.

**HOUSING:**

Composite plastic (IP20)

**NET WEIGHT:**

PR-2910 32 Kg.  
PR-2910M 45 Kg.

**DIMENSIONS:**

See drawings

**PACKED DIMENSIONS:**

670mm X 690mm X 770mm

**GROSS WEIGHT:**

PR-2950 45 Kg.  
PR-2905M 58 KG

**DIMENSIONS**

